



908BA Thermoplastic Breathing Air Fill Hose

Meets or exceeds standard CGA G-7.1-2004 grade E breathing air, NFPA 1901, NFPA 1961 and European Directive 2002/72/EL.



- Tube:** FDA/ED Thermoplastic polymer
- Reinforcement:** Kevlar®
- Cover:** Gray, abrasion resistant, perforated marine grade urethane (other colors available upon request)
- Temperature:** -40°C to +100°C (-40°F to +212°F) and fire resistant fluids up to (+70°C/158°F)
- Packaging:** Reels
- Application:** Air compressor stations, SCUBA refilling station, mobile cascade systems.

PART NUMBER	HOSE I.D.	HOSE O.D.		MAX W.P. (psi)	MIN. BURST PRESSURE (psi)	MIN. BEND RADIUS		WEIGHT (lbs/ft)	ONE PIECE
	(in)	(in)	(mm)			(in)	(mm)		COUPLINGS
908BA-03	3/16	0.41	10.5	6,000	24,000	1.38	35.0	0.06	P
908BA-04	1/4	0.50	12.7	6,000	24,000	1.97	50.0	0.07	P
908BA-06	3/8	0.63	16.0	6,000	24,000	2.95	75.0	0.10	P

Caution: Not for use as part of SCUBA systems or for use with pure oxygen and hydrogen transfer